



Penguard | EXPRESS

***CORROSION PROTECTION WITH
SPEED, COLOUR AND EFFICIENCY***



Penguard | EXPRESS

Tailor corrosion protection to fit your needs!



SPEED

- Very fast dry-to-recoat
- Very fast dry-to-handle
- Fast drying in temperatures from -5°C to 40°C
- Full system completion within one day even at low temperatures



COLOUR

- For areas where exact colour match and colour stability matter, Penguard Express CF offers the following benefits:
 - Jotun Multicolour Industry tinting system gives virtually unlimited colour choice
 - Less yellowing and darkening
 - Better performance in touch up and repair work at the new construction site



EFFICIENCY

- Fast hardness development minimises damage when structures are moved and stacked
- Fast curing reduces the need for space for drying painted structures
- Low temperature cure extends production periods and also allows application in cold climates
- Extended production periods reduce heating costs, risk of errors and simplify application
- High volume solids reduces paint volume required



Penguard | EXPRESS

Penguard Express is a fast drying, high solids 2-pack epoxy coating which may be applied in high film thickness and at lower temperatures. For use as an anti-corrosive primer or intermediate coat for the protection of steel and other substrates in atmospheric exposure. The fast dry-to-recoat and dry-to-handle times allow for increased throughput and efficiency during the paint application process. Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

Penguard | EXPRESS ZP

Penguard Express ZP is pigmented with active zinc phosphate for increased corrosion protection and is the natural choice as a first coat for protection of metal structures exposed in highly corrosive environments. Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

Penguard | EXPRESS MIO

Penguard Express MIO is reinforced with micaceous iron oxide pigments for increased barrier effect. This effect is provided by overlapping layers of the MIO pigments which prevent moisture penetrating through the paint film. It further provides increased hardness and improved adhesion of subsequent coats. Available in variant compliant with the requirements for LEED 2009 (VOC content (GS11)), BREEAM and BREEAM-NOR (VOC content (EU Directive 2004/42/CE)).

Penguard | EXPRESS CF

Penguard Express CF, the most recent addition to the Penguard Express range, offers more colour stability and a wide range of colours through MCI. It offers all the benefits of Penguard Express and can be delivered in small batches.



Penguard | EXPRESS

The ideal solution for all steel substrates

Exposed Steel Structures

Steel structures which are exposed to tough atmospheric environments, need a coating system that provides long term, durable protection.



Typically the coating system can be based on a zinc rich primer, 1 or 2 coats of high build epoxy with a topcoat. Penguard Express will provide strong adhesion to both the zinc primer and the topcoat giving excellent protection.

By using Penguard Express it is possible to apply even a 3 coat system in one day. At 10°C this can be completed within 10 hours. In warmer climates where the steel substrate may reach 40°C, it can even be completed in less than 3 hours.

Structural Steelwork

Structural steel for infrastructure projects is usually protected with one or two coats of an epoxy eventually with a topcoat.

Application of a 2 coat Penguard Express coating system can be completed within 8 hours at 10°C or within just 2 hours should the temperature reach 40°C.



Where colour and colour stability matter

Penguard Express CF meets our customers' needs for a fast curing epoxy coating that is available in a wide range of colours.

Penguard Express CF meets the demands for a more colour stable epoxy coating combined with excellent anticorrosive properties.

Penguard Express CF can be used direct to steel and in one coat application.



Product data

	Penguard Express	Penguard Express ZP	Penguard Express MIO	Penguard Express CF	
Dry film thickness μm (min – max)	75 – 250	75 – 250	75 – 250	100 – 250	
Solids (vol%)	74 \pm 2	74 \pm 2	74 \pm 2	77 \pm 2	
VOC g/l (EPA Method 24)	260	260	260	231	
Pot life	2 hr	2 hr	2 hr	1 hr	
Colours	Grey, Grey XO, Red, Buff, Light Red	Grey, Red	Grey, Red	Wide choice with MCI tinting system	
Mixing ratio	4 parts Comp. A (base) 1 part Comp. B (curing agent)				
Pot life (23°C)	2 hours (reduced at higher temperature)			1 hour	
Drying times	Surface Dry		Dry to recoat (min)	Surface Dry	Dry to recoat (min)
	40°C	0.5 hr	1 hr	1 hr	1.5 hrs
	23°C	1 hr	2 hrs	2.5 hrs	3 hrs
	10°C	2 hrs	4 hrs	4.5 hrs	6 hrs
	0°C	11 hrs	14 hrs	16 hrs	24 hrs
	-5°C	16 hrs	24 hrs	-	-

Typical systems

There are many factors influencing the choice of coatings for protection of a steel structure. Penguard range of products can be applied in a wide range of situations.

Any Penguard Express variant can be used in the system examples shown.

Used in combination with zinc rich primers, the service life of the coating system will be prolonged in higher corrosive areas.

In UV exposed areas and where long colour and gloss durability are required, a high performance topcoat should be used.

ONE COAT APPLICATION FOR LOWER CORROSIVE AREAS

Product	Coats	DFT μm
Penguard Express	1	80*

SYSTEMS FOR MEDIUM CORROSIVE AREAS

Product	Coats	DFT μm
Penguard Express	1	175

Product	Coats	DFT μm
Penguard Express	1	80*
Penguard Express	1	80*

TWO OR THREE COAT SYSTEMS FOR HIGH AND VERY HIGH CORROSIVE AREAS

Product	Coats	DFT μm
Penguard Express	1	160
Penguard Express	1	160

Product	Coats	DFT μm
Barrier 80	1	60
Penguard Express	1	100
Penguard Express	1	100

*Penguard Express CF: Min. 100 μm DFT



Penguard | EXPRESS

Delivering speed, colour and efficiency to the production process

Reduced recoating times and shorter dry-to-handle periods save time, lower costs and increase output

- Speeds up the production process and improves efficiency for applicators, contractors and steel fabricators
- Saves heating costs
- Reduces risk of errors and simplifies application by using same curing agent at low and high temperatures
- Easy to apply. Can also be applied by brush and roller
- Save coats and processing times by using any Penguard Express variant as single coat, primer or intermediate coat

Penguard Express CF provides wider choice of colours and better colour stability

- More colour stable than other fast curing epoxy primers especially in non-UV exposed areas
- Can be applied directly to metal or as part of a system
- Provides all the benefits of Penguard Express and can be delivered fast and in small batches anywhere
- Provides fast handling, simplifies logistics and improves performance in touch up and repair work at the new construction site



Jotun Protects Property

A global provider of coatings



Jotun is one of the world's leading manufacturers of paints, coatings and powder coatings.

We have 68 companies in 43 countries and 33 production facilities in 20 countries on all continents, and are represented in more than 90 countries with our network of agents, branch offices, distributors and sales offices around the world.

Our operations cover development, production, marketing, R&D and sales of paints and coatings to protect and decorate surfaces in residential, shipping and industrial markets.

UNIFORM STANDARD ACROSS THE GLOBE



- Easy to exchange trained technical personnel across national borders and multi-national projects.
- Compulsory training for all technical and sales personnel in marine and protective segments. Most of our coating advisors and technical personnel have FROSIO and/or NACE certification.
- Same competence in maintaining company standard procedures globally.

Jotun GreenSteps

FOR A MORE COLOURFUL WORLD, WE ALL NEED TO BE A LITTLE GREENER

Jotun recognises the responsibility it has to the environment and has established its own GreenSteps programme.

Through the GreenSteps programme we address market demand for more sustainable coatings solutions.



Jotun Marine Coatings and Jotun Protective Coatings offices worldwide

Legal Jotun entities worldwide are listed. For details of Branch offices and Jotun representation in countries not listed, please visit jotun.com

AUSTRALIA

Jotun Australia Pty. Ltd.,
P.O. Box 105, Altona North,
9 Cawley Road,
BROOKLYN, VIC 3025
Tel: +61 3 9314 0722
Fax: +61 3 9314 0423

BRAZIL

Jotun Brasil Ltda.
Estrada Ademar Ferreira Torres 250
Caluge - Itaboraí (RJ) CEP 24808-520
RIO DE JANEIRO
Tel: +55 21 3147 3850
Fax: +55 21 3147 3861

CYPRUS

Jotun Cyprus Ltd.
56 Theodorou Potamianou
Aphrodite Court, 1st Floor
4155, Kato Polemidia
LIMASSOL
Tel: +357 25 374455 / 374440 / 374477
Fax: +357 25 374400

P.R. of CHINA

Jotun Coatings (Zhangjiagang) Co. Ltd.
Jotun COSCO Marine Coatings
(Qingdao) Co. Ltd.
Floor 20, Jiu Shi Mansions,
No. 28 Zhong Shan Road (South)
SHANGHAI 200010
Tel: +86 21 6333 080 0
Fax: +86 21 6326 968 6

Jotun Coatings (Zhangjiagang) Co. Ltd.
Jotun COSCO Marine Coatings
(Qingdao) Co. Ltd.
Room 709-12, Goldlion Digital Network
Centre, 138 Tiyu Road East,
GUANGZHOU, 510620
Tel: +86 20 38 78 07 49
Fax: +86 20 38 78 19 66

HONG KONG

Jotun COSCO Marine Coatings (H.K.) Ltd
Room 902, 9/F,
101 King's Road, North Point
HONG KONG
Tel: +852 2527 6466
Fax: +852 2861 1307

DENMARK

Jotun Danmark A/S Jotun Coatings
Columbusvej 5, 2860 Søborg,
COPENHAGEN
Tel: +45 4492 9400
Fax: +45 4492 9401

EGYPT

El Mohandes Jotun S.A.E.
Plot 193, Second District,
City Center, Fifth Settlement,
NEW CAIRO
Tel: +202 2614 9999
Fax: +202 2614 9998

FINLAND

Nor-Maali OY
Vanhatie 20, 15240 LAHTI
Tel: +358 3 874 650
Fax: +358 3 874 6550

FRANCE

Jotun France S.A.
22/24 Rue du President Wilson, Bat.A
92300 LEVALLOIS PERRET
Tel: +33 1 4519 3882
Fax: +33 1 4519 3894

GERMANY

Jotun (Deutschland) GmbH
Haferweg 38
22769 HAMBURG
Tel: +49 40 851 960
Fax: +49 40 856 234

GREAT BRITAIN

Jotun Paints (Europe) Ltd.
Stather Road, Flixborough,
SCUNTHORPE DN15 8RR
Tel: +44 1724 400 000
Fax: +44 1724 400 100

GREECE

Jotun Hellas Ltd.
33, Zeppou Street,
Glyfada
ATHENS 16675
Tel: +30 210 42 85 980-82
+30 210 42 86 035-37
Fax: +30 210 42 85 983/
+30 210 42 87 237

INDIA

Jotun India Pvt Ltd.
502, 5th Floor,
Boston House,
Suren Road,
Behind Cinemax Theatre,
Andheri East,
Mumbai - 400 093
Tel: +91 22 2822 4600
+91 22 2820 5900 (+fax)
Fax: +91 22 2820 5900

INDONESIA

P.T. Jotun Indonesia
Kawasan Industri MM2100
Blok KK-1, Cikarang Barat
Bekasi 17520
Tel: +62 21 8998 2657
Fax: +62 21 8998 2658

IRELAND

Jotun (Ireland) Ltd.,
Unit K7, Marina Commercial Park,
Centre Park Road, CORK
Tel: +353 214 965955
Fax: +353 214 965992

ITALY

Jotun Italia S.P.A.
Via Petronio, 8, Zona Ind. Noghese
34147 - MUGGIA (TRIESTE)
Tel: +39 040 23 98204
Fax: +39 040 23 98222

JAPAN

NKM Coatings Co., Ltd.
12-1, Minamirokugo 3-chome,
Ota-ku,
TOKYO 144-0045
Tel: +81 3 6758 2212
Fax: +81 3 6758 2213

KOREA (SOUTH)

Chokwang-Jotun Ltd.
30th Block Jisa Science Park,
1205 Jisa-dong, Gangseo-gu,
BUSAN 618-230
Tel: +82 517 976 000
Fax: +82 517 117 735

LIBYA

Jotun Libya J.S.Co
Almumtaz Co. S.A. (Jotun).
Alseka Street
P.O. Box 6850
TRIPOLI
Tel: +218 214777811
Fax: +218 214780718

MALAYSIA

Jotun Paints (Malaysia) Sdn. Bhd.
Lot 7 Persiaran Perusahaan,
Section 23, P.O. Box 7050
40700 SHAH ALAM
Tel: +60 351 235 500
Fax: +60 351 235 632

THE NETHERLANDS

Jotun B.V.
Postbus 208
3200 AE SPIJKENISSE
Visiting address:
Curieweg 11b, 3208 KJ Spijkenisse
ROTTERDAM
Tel: +31 181 678 300
Fax: +31 181 617 899

NORWAY

Jotun A/S
P.O. Box 2021,
3202 SANDEFJORD
Visiting address:
Hystadveien 167, 3209 Sandefjord
Tel: +47 33 45 70 00
Fax: +47 33 45 79 00

OMAN

Jotun Paints Co. LLC
Rusayl Ind. Estate, Road No.10
P.O. Box 672 Code 111, MUSCAT
Tel: +968 2444 6100
Fax: +968 2444 6105

PAKISTAN

Jotun Pakistan (Pvt.) Ltd.
2KM Defence Road, Off 9KM Raiwind
Road, Adjacent Valencia Homes Gate
LAHORE 544770
Tel: +92 423 532 350 0-3
Fax: +92 423 532 1387

PHILIPPINES

Jotun (Philippines) Inc.
846 West Service Road, Km.18
South Super Highway
Paranaque City,
METRO MANILA 1714
Tel: +63 2239 1032-34
Fax: +63 2822 0760

POLAND

Jotun Polska Sp.zo.o.
ul. Magnacka 15,
80-180 GDAŃSK KOWALE
Tel: +48 58 555 1515
Fax: +48 58 781 9692

RUSSIA

Jotun Paints O.O.O.
Varshavskaya Str., 23/2, Office 75
196128 ST. PETERSBURG
Tel: +7 812 640 00 80
Fax: +7 812 640 00 81

SAUDI ARABIA

Jotun Saudia Co. Ltd.
Jeddah Industrial City, Phase 3,
P.O. Box 34698, JEDDAH 21478
Tel: +966 2635 0535 / 2636 1271
Fax: +966 2636 2483

SINGAPORE

Jotun (Singapore) Pte. Ltd.
37 Tuas View Crescent
Singapore 637236
Tel: +65 650 882 88
Fax: +65 6265 7484

SOUTH AFRICA

Jotun Paints South Africa (PTY) Ltd.
Wimbledon Road, P.O.Box 187
BLACKHEATH 7581
Tel: +27 21 905 1070
Fax: +27 21 905 1652

SPAIN

Jotun Iberica S.A.
Poligon Santa Rita,
Calle Estatica no. 3,
08755 Castellbisbal,
BARCELONA
Tel: +34 937 711 800
Fax: +34 937 711 801

SWEDEN

Jotun Sverige AB
P.O. Box 151, Klangfärgsgatan 13,
421 22 VÄSTRA FRÖLUNDA
Tel: +46 3169 6300
Fax: +46 3169 6397

THAILAND

Jotun Thailand Ltd
Amata Nakom Ind. Estate (BIPII)
700/353 Moo 6 Tumbol
Donhualoh, Amphur Muang
CHONBURI 2000
Tel: +66 2 022 9888
Fax: +66 38 214 373/375

TURKEY

Jotun Boya San. ve Ticaret. A.S.
Balabandere Caddesi Hilpark Suites Sitesi No.10,
Istinye 34460 Sariyer
ISTANBUL
Tel: +90 21 2279 7878
Fax: +90 21 2279 2549

U. A. E.

Abu Dhabi
Jotun Abu Dhabi (LLC)
P.O. Box 3714, Mussafah
ABU DHABI
Tel: +971 2691 0700
Fax: +971 2551 0232

Dubai

Jotun U.A.E. Ltd. (LLC)
P.O. Box 3671,
Al Quoz Industrial Area
DUBAI
Tel: +971 4339 5000
Fax: +971 4338 0666

USA

Jotun Paints Inc.
9203 Highway 23, P.O. Box 159,
Belle Chasse, LA 70037
Tel: +1 713 860 8241
Fax: +1 713 860 8242

VIETNAM

Jotun Paints (Vietnam) Co. Ltd.
Song Than Industrial. Zone,
No.1 Street 10,
Di An District, Binh Duong Province
Tel: +84 650 3742206
Fax: +84 650 374 2205

YEMEN

Jotun Yemen Paints Co. Ltd
P.O. Box 70183, Al Alam
ADEN
Tel: +967 2820 546-9
Fax: +967 2249 362

Jotun A/S

P.O. Box 2021,
N-3202 Sandefjord, Norway
Tel: +47 33 45 70 00
jotun.com



Jotun Protects Property